



BEHR MARQUEE® Ceiling Flat

- One-Coat Hide Guaranteed
- Stain-Blocking Paint & Primer in One
- Spatter & Drip Resistant
- Tintable to more than 200 One-Coat Colors

- Antimicrobial-Mildew Resistant Finish
- Low VOC, 100% Acrylic
- Lifetime Warranty*

No. 1458 PURE WHITE



1 Hr Dry Time
2 Hr Recoat Time



250-400 Sq. Ft.
Coverage



Soap & Water
Clean-Up



Protect
from Freezing

BEHR MARQUEE®

BEHR MARQUEE Stain-Blocking Paint & Primer Ceiling Flat is part of Behr's most advanced paint offering. It features guaranteed one-coat hide plus an exclusive MARQUEE Interior One-Coat Color Collection. This 100% acrylic, antimicrobial-mildew resistant finish makes MARQUEE Ceiling Paint ideal for every room

WHERE TO USE

Apply on Properly Coated Drywall/Gypsum Board, Plasterboard and Cured Plaster.

PREPARATION & PRIME

- Properly prepare and clean all surfaces.
- Remove loose paint, wash off dirt and grease with detergent, rinse and allow to dry.
- Remove mildew stains with a mildew stain remover.
- Scuff sand glossy surfaces and repair imperfections.
- Remove all dust with a damp cloth, allow to dry.
- Allow new stucco, plaster and masonry to cure for 30 days before painting.
- Darker colors may require additional dry time between coats.

STAINED SURFACES

- Use MARQUEE Paint as a primer for properly prepared uncoated, glossy, porous or repaired ceilings.

STAINED SURFACES

- Lock in water stains with MARQUEE Ceiling Paint as a spot primer.
- For heavy stains, test for stain bleed-through by applying MARQUEE Ceiling Paint to a small section. If the stain bleeds through, spot prime with another coat to the stained area and test again before topcoating. If bleeding continues, a longer dry time is needed before topcoating.

***LIFETIME LIMITED WARRANTY** Behr Process Corporation warrants to the original residential consumer purchaser the performance of this product as described on this label for so long as you reside in your home. THIS WARRANTY IS NOT VALID WHEN THE PRODUCT IS NOT PROPERLY APPLIED TO A PROPERLY PREPARED SURFACE OR CARED FOR IN ACCORDANCE WITH THE LABEL DIRECTIONS. This warranty is not transferable. If this product is found not to perform as specified upon inspection by our representative during the warranty period, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

APPLICATION

Apply when air and surface temperatures are between 50-90°F (10-32°C).

- Stir paint occasionally.
- Intermix containers of same product to ensure color and sheen uniformity.
- Use a high quality 3/8-1/2" nap roller cover, nylon/polyester brush or an airless sprayer (.015-.019" spray tip, 60 mesh filter).
- Popcorn style acoustic ceilings; use acoustic ceiling roller cover (1/2-3/4" nap) or airless sprayer (.015-.019" spray tip, 60 mesh filter).
- Allow new stucco, plaster and masonry to cure for 30 days before painting.
- Darker colors may require additional dry time between coats.
- Cooler temperatures or higher humidity may prolong drying time.

DISPOSAL

For disposal of empty containers, unused paint and soiled rags, contact your household refuse collection service.

Visit Behr.com for painting tips, expert project advice and the perfect color coordination with the ColorSmart by BEHR® Tool.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING Cancer and Reproductive Harm – www.P65Warnings.ca.gov

CAUTION! IRRITANT! HARMFUL IF SWALLOWED. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.



©2017 Behr Process Corporation
Santa Ana, CA 92704 U.S.A. • behr.com
V.O.C. (C.O.V.) <50 g/L • REV. 08/17** 3 Hr Recoat Time for Deep Base only